

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M1413

051712216791

100 mm

53 mm

21 mm

147.3 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

78 mm

No

AC

40 A

DIN 43653 TN/80 Type T Indicator for Micro

Other

000

690 V (IEC), 700 V (UL)

Top fuse status indicator

460 at 660 V

690 V

None

Blade end x blade end

M8

gR (general purpose semiconductor protection)

12 W

Fuse

Square body, slotted offset bolted tags

200 kA

Class gR

69

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard