

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M1319

051712216555

105 mm

46 mm

300 mm

131 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

76.7 mm

No

AC

160 A

DIN 43653 U/80 Without indicator Bolted tag

Other

000

690 V (IEC), 700 V (UL)

None

16000 at 660 V

690 V

Blade end x blade end

M8

aR (accompanied semiconductor protection)

32 W

Fuse

Square body, slotted offset bolted tags

200 kA

Class aR

2300

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard