

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M1565D

051712334778

79 mm

51 mm

21 mm

134.8 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

No

AC

63 A

DIN 43620 Bladed

Other

Dual indicator

000

690 V (IEC), 700 V (UL)

Combination fuse status indicator

1550 at 660 V

690 V

None

Din 43-620 blade end x Din 43-620 blade end

gR (general purpose semiconductor protection)

11.5 W

Fuse

Square body, knife blade contacts

200 kA

Class gR

215

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard