

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Application

Voltage type  
Packaging type

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M1572D

051712334938

79 mm

69 mm

30 mm

204 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

No

AC

315 A

DIN 43620 Bladed

Other

Dual indicator

00

690 V (IEC), 700 V (UL)

Combination fuse status indicator

84500 at 660 V

690 V

None

Din 43-620 blade end x Din 43-620 blade end

aR (accompanied semiconductor protection)

45 W

Fuse

Square body, knife blade contacts

200 kA

Class aR

12000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard