

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Compliances
- Certifications
- Fuse indicator
- Interrupt rating
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Insulated metal gripping lugs (IMGL)
- Connection
- Current type
- Amperage Rating
- Utilization category
- Watt losses
- Fuse type
- Type
- Fuse shape
- Breaking capacity
- Fuse size
- Class
- Pre arc (I2T)
- Voltage rating
- Application

产品规格

2D 平面图
Date

Voltage type
1400DIM-15
Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse
170M1364
051712216654
105 mm
46 mm
300 mm
133.2 g
RoHS Compliant CE Marked
IEC Rated UL Recognized
Top fuse status indicator
200 kAIC
Other
770 at 660 V
690 V
None
No
Blade end x blade end
AC
50 A
gR (general purpose semiconductor protection)
15 W
DIN 43653 /80 Visual indicator
Fuse
Square body, slotted offset bolted tags
200 kA
000
Class gR
115
690 V (IEC), 700 V (UL)
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers