

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Connection
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Mon Oct 23 2023

Eaton Bussmann series high speed square body fuse

170M1419

051712216852

100 mm

53 mm

21 mm

135 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

78 mm

No

AC

160 A

DIN 43653 TN/80 Type T Indicator for Micro Bolted

tag

Other

000

690 V (IEC), 700 V (UL)

Top fuse status indicator

16000 at 660 V

690 V

None

Blade end x blade end

M8

aR (accompanied semiconductor protection)

32 W

Fuse

Square body, slotted offset bolted tags

200 kA

Class aR

2300

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard