

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M2614

051712792349

233 mm

66 mm

140 mm

213.5 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

78 mm

No

AC

100 A

DIN 43653 /80 Visual indicator

Other

00

690 V (IEC), 700 V (UL)

Top fuse status indicator

4150 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

20 W

Fuse

Square body, slotted offset bolted tags

200 kA

Class aR

620

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard