

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse
170M2719
051712816656
30 mm
62 mm
64 mm
211 g
Not Applicable
CE Marked RoHS Compliant
UL Recognized IEC Rated
200 kAIC

No
AC
DIN 43 620 Flush
315 A
Flush end 00B/60 Visual indicator
IEC 60269-4 flush end connections type A
00
690 V (IEC)
Top fuse status indicator

68500 at 660 V
690 V
None
M8
aR (accompanied semiconductor protection)
55 W
Fuse
Square body, flush end contacts
200 kA
Class aR
10000
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard