

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Compliances
- Certifications
- Fuse indicator
- Interrupt rating
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Insulated metal gripping lugs (IMGL)
- Connection
- Current type
- Amperage Rating
- Utilization category
- Watt losses
- Fuse type
- Type
- Fuse shape
- Breaking capacity
- Fuse size
- Class
- Pre arc (I2T)
- Voltage rating
- Application

产品规格

Date

Voltage type
Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M2669

051712799195

98 mm

51 mm

28 mm

211.833 g

RoHS Compliant CE Marked

IEC Rated UL Recognized

Other

200 kAIC

68500 at 660 V

690 V

None

No

Blade end x blade end

AC

315 A

aR (accompanied semiconductor protection)

55 W

DIN 43653 TN/80 Type T Indicator for Micro

Fuse

Square body, slotted offset bolted tags

200 kA

00

Class aR

10000

690 V (IEC), 700 V (UL)

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers