

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of
connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M2716

051712254359

75 mm

77 mm

163 mm

211 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

64 mm

No

AC

DIN 43 620 Flush

160 A

Flush end 00B/60 Visual indicator

IEC 60269-4 flush end connections type A

00

690 V (IEC)

Top fuse status indicator

13000 at 660 V

690 V

None

M8

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, flush end contacts

200 kA

Class aR

1900

semiconductor protection

Standard