

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Fitted with:  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I<sup>2</sup>T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
  
Used with  
  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I<sup>2</sup>T)  
Application  
Voltage type  
Packaging type  
Tue Oct 24 2023

Date

Eaton Bussmann series high speed traction fuse  
170M2045  
051712422130  
217 mm  
89 mm  
164 mm  
4612 g  
No warranty  
Not Applicable RoHS Compliant  
IEC Rated  
2000 V  
100 kAIC  
  
194 mm  
  
DC  
Other  
600 A  
62 Hz

Parallel double slot tags

289796 at 2000 Vdc  
None  
Ceramic  
M8  
aR (accompanied semiconductor protection)  
305 W  
Fuse  
Square body, parallel bolted tags  
Protection of DC third rail applications up to  
2000 Vdc  
100 kA  
45 Hz  
Class aR  
188179  
traction third rail

Standard