

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Connection
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Eaton Bussmann series high speed square body fuse

170M2710

051712254304

75 mm

77 mm

163 mm

211 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

64 mm

No

AC

DIN 43 620 Flush

40 A

Flush end 00B/60 Visual indicator

IEC 60269-4 flush end connections type A

00

690 V (IEC)

Top fuse status indicator

360 at 660 V

690 V

None

Blade end x blade end

M8

gR (general purpose semiconductor protection)

9 W

Fuse

Square body, flush end contacts

200 kA

Class gR

50

semiconductor protection

AC/DC

Standard