

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

Date

Tue Oct 24 2023

Eaton Bussmann series high speed square body fuse

170M2692

051712540261

217 mm

65 mm

85 mm

218 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

No

AC

16 A

DIN 43620 T indicator for micro Bladed

Other

Type T Indicator for micro

00

690 V (IEC)

Top fuse status indicator

38 at 600 V

690 V

None

Blade end x Din 43-620 blade end

gR (general purpose semiconductor protection)

5.5 W

Fuse

Square body, knife blade contacts

200 kA

Class gR

7.2

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard