

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Rated voltage DC  
Interrupt rating  
Center-to-center distance of connections  
Current type  
Release characteristic  
Amperage Rating  
Frequency rating - max  
Fuse system (according to IEC 60269)  
Rated switching capacity  
Fuse size  
Voltage rating  
Fuse indicator  
Special features  
Construction size  
Clearing (I<sup>2</sup>T)  
Color  
Material  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Frequency rating - min  
Class  
Pre arc (I<sup>2</sup>T)  
Application  
Voltage type  
Packaging type

Date

Tue Oct 24 2023

Eaton Bussmann series high speed traction fuse  
170M2016  
051712391382  
131 mm  
88 mm  
75 mm  
2294 g  
Not Applicable

IEC  
750 V  
110 kAIC  
129 mm  
DC  
Other  
800 A  
62 Hz  
IEC 60269-4 flush end connections type A  
110 A  
3

Flush End Fuse Link

1450000 at 750 Vdc  
None  
Ceramic

gR (general purpose semiconductor protection)  
178 W  
Fuse  
Square body, flush end contacts  
110 kA  
45 Hz  
Class gR  
349900  
traction third rail

Standard