

常用规格

- Product Name
- Catalog Number
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Compliances
- Certifications
- Rated voltage DC
- Interrupt rating
- Center-to-center distance of connections
- Current type
- Release characteristic
- Amperage Rating
- Frequency rating - max
- Fuse system (according to IEC 60269)
- Rated switching capacity
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Color
- Material
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Frequency rating - min
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Tue Oct 24 2023

Eaton Bussmann series high speed traction fuse

170M2005

130 mm

59 mm

41 mm

2294 g

CE RoHS

IEC 60269-4

750 V

85 kA at 750 Vdc, 80 kA at 950 Vdc

128 mm

DC

Other

160 A

62 Hz

IEC 60269-4 flush end connections type A

80 A

1*

18250 at 750 Vdc

None

Ceramic

M8

aR (accompanied semiconductor protection)

56 W

Fuse

Square body, flush end contacts

85 kA

45 Hz

Class aR

5500

traction third rail

Standard