

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Compliances
- Certifications
- Rated voltage DC
- Interrupt rating
- Center-to-center distance of connections
- Current type
- Release characteristic
- Amperage Rating
- Frequency rating - max
- Fuse system (according to IEC 60269)
- Rated switching capacity
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Color
- Material
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Frequency rating - min
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Tue Oct 24 2023

Eaton Bussmann series high speed traction fuse

170M2100

051712771016

164 mm

66 mm

39 mm

0.001 g

CE RoHS Compliant EAC

IEC 60269-4

1200 V

50 kAIC

139.5 mm

DC

Other

20 A

62 Hz

150 A

Single slot tags

1\*

249 at 1200 Vdc

None

Ceramic

M8

aR (accompanied semiconductor protection)

2 W

Fuse

Square body, offset bolted tags

100 kA

45 Hz

Class aR

82

traction third rail

Standard