

常用规格

产品规格

Date

- Product Name
 - Catalog Number
 - Product Length/Depth
 - Product Height
 - Product Width
 - Product Weight
 - Certifications
 - Rated voltage DC
 - Interrupt rating
 - Center-to-center distance of connections
 - Current type
 - Release characteristic
 - Amperage Rating
 - Frequency rating - max
 - Fuse system (according to IEC 60269)
 - Fitted with:
 - Voltage rating
 - Fuse indicator
 - Construction size
 - Clearing (I2T)
 - Color
 - Material
 - Mounting dimension
 - Utilization category
 - Watt losses
 - Type
 - Fuse shape
 - Breaking capacity
 - Frequency rating - min
 - Class
 - Pre arc (I2T)
 - Application
 - Voltage type
 - Packaging type
- Tue Oct 24 2023

Eaton Bussmann series high speed traction fuse

170M2050

216 mm

66 mm

39 mm

461.2 g

IEC 60269-4

2000 V

100 kAIC

197 mm

DC

Other

50 A

62 Hz

Single slot tags

1

1780

None

Ceramic

M8

aR (accompanied semiconductor protection)

33 W

Fuse

Square body, offset bolted tags

100 kA

45 Hz

Class aR

610

traction third rail

Standard