

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Wed Oct 25 2023

Eaton Bussmann series high speed square body fuse
170M3469
051712217194
60 mm
50 mm
43 mm
266.5 g
Not Applicable
CE Marked RoHS Compliant
IEC Rated UL Recognized
200 kAIC

No
AC
Flush
400 A
Flush end BKN/Type K Indicator for Micro
IEC 60269-4 flush end connections type A
Type K Indicator for micro
1*
690 V (IEC), 700 V (UL)
Centre fuse status indicator
Other
105000 at 660 V
690 V
None
M8
aR (accompanied semiconductor protection)
60 W
Fuse
Square body, flush end contacts
200 kA
Class aR
77
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard