

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Clearing loss
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Wed Oct 25 2023

Eaton Bussmann series high speed square body fuse

170M3267

051712255516

290 mm

62 mm

142 mm

0.322 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

50

106 mm

No

AC

DIN 43 620

315 A

Bolted tag DIN 43653

Other

1*

690 V

Centre fuse status indicator

46500 at 660 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

50 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

7000

semiconductor protection

Standard