

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Clearing loss
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

Date

Voltage type
Packaging type
Wed Oct 25 2023

Eaton Bussmann series high speed square body fuse

170M3008

051712254533

104 mm

58 mm

45 mm

0.287 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

9

76.5 mm

No

AC

40 A

DIN 43653 /80 Visual indicator Bolted tag

Other

1*

690 V (IEC), 700 V (UL)

Top fuse status indicator

270 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

9 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

40

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard