

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Wed Oct 25 2023

Eaton Bussmann series high speed square body fuse

170M3316

051712255653

305 mm

65 mm

145 mm

301 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

76 mm

No

AC

250 A

French style E/Type indicator for micro Bolted
tag

Other

Type T Indicator for micro

1*

690 V

Top fuse status indicator

28500 at 660 V

None

M8

aR (accompanied semiconductor protection)

40 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

4200

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard