

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Clearing loss
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3211

051712255189

305 mm

65 mm

145 mm

347 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

18

108 mm

No

AC

80 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

690 V (IEC), 700 V (UL)

Top fuse status indicator

1250 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

18 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

185

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard