

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Date

Application  
Voltage type  
Packaging type  
Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3814D

051712334020

135 mm

64 mm

40 mm

423.3333333 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

No

AC

160 A

DIN 43620 Bladed

Other

Dual indicator

1

690 V (IEC), 700 V (UL)

Combination fuse status indicator

8250 at 660 V

690 V

None

Din 43-620 blade end x Din 43-620 blade end

aR (accompanied semiconductor protection)

12 W

Fuse

Square body, knife blade contacts

200 kA

Class aR

1150

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard