

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3460

051712799928

193 mm

47 mm

106 mm

261.5 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

50 mm

No

AC

Flush

63 A

Flush end BKN/Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

Other

770 at 660 V

690 V

None

M8

aR (accompanied semiconductor protection)

14 W

Fuse

Square body, flush end contacts

200 kA

Class aR

115

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard