

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3717

051712256995

96 mm

50 mm

170 mm

174.5 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

117 mm

No

AC

315 A

US Style FU/115 without indicator Bolted tag

Other

1\*

690 V

None

46500 at 660 V

Blade end x blade end

M10

aR (accompanied semiconductor protection)

50 W

Fuse

Square body, center bolted tags

200 kA

Class aR

7000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard