

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3512

051712256377

155 mm

45 mm

90 mm

525 g

RoHS Compliant EAC CE

IEC 60269-4 UL 248-13

200 kAIC

50 mm

No

AC

Flush

100 A

Flush end G/Visual indicator

Other

1*

690 V (IEC), 700 V (UL)

Top fuse status indicator

2450 at 660 V

690 V

None

aR (accompanied semiconductor protection)

21 W

Fuse

Square body, flush end contacts

200 kA

Class aR

360

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard