

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3972

051712678933

290 mm

62 mm

142 mm

272 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

125 kAIC

106 mm

No

AC

250 A

DIN 43653 KN/110 Type K Indicator for Micro

Other

1*

1000 V (IEC)

Centre fuse status indicator

57000 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

48 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

9550

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard