

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3986

051712679022

305 mm

65 mm

145 mm

171 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

125 kAIC

108 mm

No

AC

160 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1*

1000 V (IEC)

Top fuse status indicator

17500 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

45 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

2850

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard