

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Clearing loss
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Connection
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)

产品规格

Date

Application

Voltage type

Packaging type

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3122

051712254915

290 mm

62 mm

142 mm

310 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

75

76.4 mm

No

AC

DIN 43 620

550 A

DIN 43653 KN/80 Type K Indicator for Micro Bolted

tag

Other

1\*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

230000 at 660 V

690 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

75 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

34000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard