

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse
170M3495
051712256308
43 mm
74 mm
60 mm
0.001 g
RoHS Compliant EAC CE
IEC 60269-4 UL 248-13
100 kAIC

No
AC
Flush
250 A
Flush end GKN/75 Type K indicator for micro
Other
Type K Indicator for micro
1*
1250 V (IEC), 1300 V (UL)
Centre fuse status indicator

54500 at 1000 V, 73000 at 1250 V
1250 V
None

aR (accompanied semiconductor protection)
55 W
Fuse
100 kA
Class aR
9200
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers
AC/DC
Standard