

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3771

051712257282

92 mm

60 mm

163 mm

176 g

RoHS Compliant EAC CE

IEC 60269-4

200 kAIC

117 mm

No

AC

500 A

US Style FKE/115 Type K indicator for micro

Other

Type K Indicator for micro

1*

690 V

Centre fuse status indicator

180000 at 660 V

None

M10

aR (accompanied semiconductor protection)

70 W

Fuse

Square body, center bolted tags

200 kA

Class aR

27000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard