

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

产品规格

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3667

051712815178

305 mm

65 mm

145 mm

319 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

78.5 mm

No

AC

315 A

US Style FKE/Type K indicator for micro Bolted
tag

Other

Type K Indicator for micro

1*

690 V

Centre fuse status indicator

46500 at 660 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

50 W

Fuse

Square body, center bolted tags

200 kA

Class aR

7000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard