

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Warranty
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application

产品规格

Date

Voltage type
Packaging type
Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3443

051712256148

62 mm

90 mm

152 mm

370 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

100 kAIC

74 mm

No

AC

Flush

160 A

Flush end BKN/80 Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

16000 at 1000 V, 21000 at 1250 V

1250 V

None

M8

aR (accompanied semiconductor protection)

30 W

Fuse

Square body, flush end contacts

100 kA

Class aR

2600

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard