

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
  
Fuse type  
  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
  
Application  
  
Voltage type  
Packaging type

产品规格

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3189

051712255059

305 mm

65 mm

145 mm

417 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

100 kAIC

108 mm

No

AC

63 A

DIN 43653 TN/110 Type T Indicator for Micro

Bolted tag

Other

1\*

1250 V (IEC), 1300 V (UL)

Top fuse status indicator

1300 at 1000 V, 1750 at 1250 V

1250 V

None

M10

aR (accompanied semiconductor protection)

20 W

Fuse

Square body, slotted center bolted tags

100 kA

Class aR

215

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard