常用规格	Product Name
	Catalog Number
	UPC Product Longth/Donth
	Product Length/Depth Product Height
	Product Width
	Product Weight
	Warranty
	Compliances
	Certifications
产品规格	Interrupt rating
	Center-to-center distance of
	connections
	Insulated metal gripping lugs (IMGL)
	Current type
	Mounting method
	Amperage Rating
	Fuse type
	Fuse system (according to IEC 60269)
	Fuse size
	Voltage rating
	Fuse indicator
	Construction size
	Clearing (I2T)
	Rated voltage AC
	Color Mounting dimension
	Mounting dimension Utilization category
	Watt losses
	Type
	Fuse shape
	Breaking capacity
	Class
	Pre arc (I2T)
	Application
	Voltage type
	Packaging type
Date	Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse 170M3990 051712679060 305 mm 65 mm 145 mm319 g Not Applicable CE Marked RoHS Compliant IEC Rated UL Recognized 125 kAIC 108 mm No AC DIN 43 620 350 A DIN 43653 TN/110 Type T Indicator for Micro Bolted tag 0ther 1*1000 V Top fuse status indicator 175000 at 1000 V None M10 aR (accompanied semiconductor protection) 65 W Fuse Square body, slotted center bolted tags 125 kA Class aR 29000 Semiconductor, DC Common bus, DC drives, power converters/rectifiers

 $\operatorname{Standard}$