

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of
connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3396

051712255936

96 mm

50 mm

170 mm

158.5 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

100 kAIC

74 mm

No

AC

Flush

315 A

Flush end BKN/75 Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

115000 at 1000 V, 150000 at 1250 V

1250 V

None

M8

aR (accompanied semiconductor protection)

60 W

Fuse

Square body, flush end contacts

100 kA

Class aR

18500

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

AC/DC

Standard