

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)

Date

Application  
Voltage type  
Packaging type  
Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3971

051712671729

290 mm

62 mm

142 mm

1.025 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

125 kAIC

106 mm

No

AC

200 A

DIN 43653 KN/110 Type K Indicator for Micro

Other

1\*

1000 V (IEC)

Centre fuse status indicator

29500 at 1000 V

1000 V

None

M10

aR (accompanied semiconductor protection)

45 W

Fuse

Square body, slotted center bolted tags

125 kA

Class aR

4950

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard