

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

Date

Thu Oct 26 2023

Eaton Bussmann series high speed square body fuse

170M3415

051712799546

155 mm

45 mm

90 mm

245.8333333 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

50 mm

No

AC

Flush

200 A

Flush end

IEC 60269-4 flush end connections type A

1\*

690 V

Top fuse status indicator

Other

15000 at 660 V

None

M8

aR (accompanied semiconductor protection)

35 W

Fuse

Square body, flush end contacts

200 kA

Class aR

2200

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard