

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Connection
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3720

051712257022

96 mm

50 mm

170 mm

175 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

117 mm

No

AC

450 A

US Style FU/115 without indicator Bolted tag

Other

1*

690 V

None

140000 at 660 V

Blade end x blade end

M10

aR (accompanied semiconductor protection)

65 W

Fuse

Square body, center bolted tags

200 kA

Class aR

21000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard