

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications

产品规格

Interrupt rating  
Center-to-center distance of connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Mounting method  
Amperage Rating  
Fuse type  
Fuse system (according to IEC 60269)  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Breaking capacity  
Class  
Pre arc (I2T)  
Application  
Voltage type  
Packaging type

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3572

051712812078

193 mm

47 mm

106 mm

262 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

50 mm

No

AC

Flush

550 A

Flush end GKN/Type K indicator for micro

Other

1\*

690 V (IEC), 700 V (UL)

Centre fuse status indicator

230000 at 660 V

690 V

None

aR (accompanied semiconductor protection)

75 W

Fuse

200 kA

Class aR

34000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard