

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3421

051712256063

155 mm

45 mm

90 mm

256 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

50 mm

No

AC

Flush

500 A

Flush end B/Visual indicator

IEC 60269-4 flush end connections type A

1*

690 V (IEC), 700 V (UL)

Top fuse status indicator

Other

180000 at 660 V

690 V

None

M8

aR (accompanied semiconductor protection)

70 W

Fuse

Square body, flush end contacts

200 kA

Class aR

27000

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard