

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of
connections
Insulated metal gripping lugs (IMGL)
Current type
Mounting method
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application

产品规格

Date

Voltage type
Packaging type
Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3439

051712256100

92 mm

60 mm

163 mm

847 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

100 kAIC

74 mm

No

AC

Flush

63 A

Flush end BKN/80 Type K Indicator for Micro

IEC 60269-4 flush end connections type A

Type K Indicator for micro

1*

1250 V (IEC), 1300 V (UL)

Centre fuse status indicator

Other

1300 at 1000 V, 1750 at 1250 V

1250 V

None

M8

aR (accompanied semiconductor protection)

20 W

Fuse

Square body, flush end contacts

100 kA

Class aR

215

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard