

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3146

051712255011

305 mm

65 mm

145 mm

0.071 kg

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

100 kAIC

107 mm

No

AC

315 A

DIN 43653 /110 Visual indicator

Other

1*

1250 V (IEC), 1300 V (UL)

Top fuse status indicator

115000 at 1000 V, 150000 at 1250 V

1250 V

None

M10

aR (accompanied semiconductor protection)

60 W

Fuse

Square body, slotted center bolted tags

100 kA

Class aR

18500

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard