

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating

Fuse type

Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Application

Voltage type
Packaging type

产品规格

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3743

051712257107

62 mm

90 mm

152 mm

975 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated CSA Certified UL Recognized

100 kAIC

116 mm

No

AC

160 A

US Style FKE/115 Type K indicator for micro

Bolted tag

Other

Type K Indicator for micro

1*

1250 V

Centre fuse status indicator

16000 at 1000 V, 21000 at 1250 V

None

M10

aR (accompanied semiconductor protection)

40 W

Fuse

Square body, center bolted tags

100 kA

Class aR

2600

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

AC/DC

Standard