

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications
Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fitted with:
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)
Application
Voltage type
Packaging type

产品规格

Date

Fri Oct 27 2023

Eaton Bussmann series high speed square body fuse

170M3312

051712255615

305 mm

65 mm

145 mm

301 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated UL Recognized

200 kAIC

76 mm

No

AC

100 A

French style E/Type indicator for micro

Other

Type T Indicator for micro

1*

690 V

Top fuse status indicator

2450 at 660 V

None

M8

aR (accompanied semiconductor protection)

21 W

Fuse

Square body, slotted center bolted tags

200 kA

Class aR

360

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard