常用规格 产品规格	Product Name Catalog Number UPC Product Length/Depth Product Height Product Width Product Weight Warranty Compliances Certifications Interrupt rating Center-to-center distance of connections Insulated metal gripping lugs (IMGL) Current type Amperage Rating
	Fuse type
	Fuse system (according to IEC 60269) Fitted with: Fuse size Voltage rating Fuse indicator Construction size Clearing (I2T) Rated voltage AC Color Mounting dimension Utilization category Watt losses Type Fuse shape Breaking capacity Class Pre arc (I2T)
	Application
Date	Voltage type Packaging type Mon Oct 30 2023

Eaton Bussmann series high speed square body fuse 170M3361 051712255745 168 mm 80 mm 124 mm705 g Not Applicable CE Marked RoHS Compliant IEC Rated UL Recognized 200 kAIC 76 mm No AC 80 A French style EKN/Type K Indicator for Micro Bolted tag 0ther Type K Indicator for micro 1\*690 V Centre fuse status indicator 1250 at 660 V None M8 aR (accompanied semiconductor protection) 18 W Fuse Square body, slotted center bolted tags 200 kA Class aR 185 Semiconductor, DC Common bus, DC drives, power converters/rectifiers

 $\operatorname{Standard}$