常用规格

产品规格

Product Name

UPC

Product Length/Depth

Product Height Product Width Product Weight

Warranty Compliances Certifications Interrupt rating

Current type Amperage Rating

Fuse type

Voltage rating Fuse indicator Construction size Clearing (I2T) Rated voltage AC

Color

Mounting dimension Utilization category

Watt losses

Type

Fuse shape

Breaking capacity

Class

Pre arc (I2T)

Application

Voltage type Packaging type Mon Oct 30 2023

Date

Catalog Number

Center-to-center distance of

connections

Insulated metal gripping lugs (IMGL)

Fuse system (according to IEC 60269)

Fitted with: Fuse size

```
Eaton Bussmann series high speed square body fuse
170M3362
051712255752
168 mm
80 mm
124 \text{ mm}
705 g
Not Applicable
CE Marked RoHS Compliant
UL Recognized IEC Rated
200 kAIC
76 mm
No
AC
100 A
French style EKN/Type K Indicator for Micro
Bolted tag
Other
Type K Indicator for micro
690 V
Centre fuse status indicator
2450 at 660 V
None
aR (accompanied semiconductor protection)
21 W
Square body, slotted center bolted tags
200 kA
Class aR
360
Semiconductor, DC Common bus, DC drives, power
converters/rectifiers
```

Standard