

常用规格

Product Name  
Catalog Number  
UPC  
Product Length/Depth  
Product Height  
Product Width  
Product Weight  
Warranty  
Compliances  
Certifications  
Interrupt rating  
Center-to-center distance of  
connections  
Insulated metal gripping lugs (IMGL)  
Current type  
Amperage Rating  
  
Fuse type  
  
Fuse system (according to IEC 60269)  
Fitted with:  
Fuse size  
Voltage rating  
Fuse indicator  
Construction size  
Clearing (I2T)  
Rated voltage AC  
Color  
Connection  
Mounting dimension  
Utilization category  
Watt losses  
Type  
Fuse shape  
Breaking capacity  
Class  
Pre arc (I2T)  
  
Application  
  
Voltage type  
Packaging type

产品规格

Date

Mon Oct 30 2023

Eaton Bussmann series high speed square body fuse

170M3772

051712257299

92 mm

60 mm

163 mm

176 g

Not Applicable

CE Marked RoHS Compliant

UL Recognized IEC Rated

200 kAIC

117 mm

No

AC

550 A

US Style FKE/115 Type K indicator for micro

Bolted tag

Other

Type K Indicator for micro

1\*

690 V

Centre fuse status indicator

230000 at 660 V

None

Blade end x blade end

M10

aR (accompanied semiconductor protection)

75 W

Fuse

Square body, center bolted tags

200 kA

Class aR

34000

Semiconductor, DC Common bus, DC drives, power  
converters/rectifiers

Standard