

常用规格

- Product Name
- Catalog Number
- UPC
- Product Length/Depth
- Product Height
- Product Width
- Product Weight
- Compliances
- Certifications
- Interrupt rating
- Center-to-center distance of connections
- Insulated metal gripping lugs (IMGL)
- Current type
- Mounting method
- Amperage Rating
- Fuse type
- Fuse system (according to IEC 60269)
- Fitted with:
- Fuse size
- Voltage rating
- Fuse indicator
- Construction size
- Clearing (I2T)
- Rated voltage AC
- Color
- Mounting dimension
- Utilization category
- Watt losses
- Type
- Fuse shape
- Breaking capacity
- Class
- Pre arc (I2T)
- Application
- Voltage type
- Packaging type

产品规格

Date

Mon Oct 30 2023

Eaton Bussmann series high speed square body fuse

170M3957

051712678827

152 mm

59 mm

86 mm

0.36 kg

RoHS Compliant EAC CE

IEC 60269-4

125 kAIC

74 mm

No

AC

Flush

200 A

Flush end BKN/Type K Indicator for Micro

Other

Type K Indicator for micro

1*

1000 V (IEC)

Centre fuse status indicator

29500 at 1000 V

1000 V

None

M8

aR (accompanied semiconductor protection)

50 W

Fuse

Square body, flush end contacts

125 kA

Class aR

4950

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

Standard