

常用规格

Product Name
Catalog Number
UPC
Product Length/Depth
Product Height
Product Width
Product Weight
Warranty
Compliances
Certifications

产品规格

Interrupt rating
Center-to-center distance of connections
Insulated metal gripping lugs (IMGL)
Current type
Amperage Rating
Fuse type
Fuse system (according to IEC 60269)
Fuse size
Voltage rating
Fuse indicator
Construction size
Clearing (I2T)
Rated voltage AC
Color
Mounting dimension
Utilization category
Watt losses
Type
Fuse shape
Breaking capacity
Class
Pre arc (I2T)

Date

Application
Voltage type
Packaging type
Mon Oct 30 2023

Eaton Bussmann series high speed square body fuse

170M3696

051712256889

156 mm

59 mm

45 mm

643.5 g

Not Applicable

CE Marked RoHS Compliant

IEC Rated CSA Certified UL Recognized

100 kAIC

116 mm

No

AC

315 A

US Style FU/115 without indicator Bolted tag

Other

1*

1250 V

None

115000 at 1000 V, 150000 at 1250 V

M10

aR (accompanied semiconductor protection)

60 W

Fuse

Square body, center bolted tags

100 kA

Class aR

18500

Semiconductor, DC Common bus, DC drives, power
converters/rectifiers

AC/DC

Standard